

Installation Instructions
PART# 10900 / 10901
Wireless QTEC Controller



Thank you for your purchase of the Wireless QTEC Controller. This controller will support both single and dual Quick Time Electric Cutout applications. Your kit comes with the wireless receiver and (2) key fob style remote controllers.

Install Instructions:

1. Find a suitable secure, dry location for installation of the wireless control box. Remember you will need to supply both a 12volt power source as well as ground. Typically the wiring supplied to cigarette lighter/accessory plug or perhaps a seat heater will be perfect as the cutouts draw less than 1 amp during operation

BE SURE to run the Positive (Red) + wire to your vehicle 12v hot source and the Black (ground) wire to a suitable chassis ground. Please note, **hooking these wires up backwards will damage the receiver.**

2. After securing the receiver and connecting power and ground. Hook up your intermediate wires between the valves and receiver box. Be sure to route the intermediate wires so they don't come into contact with your exhaust system or any other area of the vehicle that could cause scraping & chaffing.

Your Done!




Operation Instructions

1. To open the cutouts, hold the OPEN button until the desired exhaust sound is achieved. It will take approx. 5-6 seconds to open the valve to the full open position

2. To close the cutouts, hold the CLOSE button until the desired exhaust sound is achieved.

TIP: For best results, lubricate the cutout valve butterflies at least monthly to keep them free of debris and carbon build up.



LEGEND

- 12v Power Input
- 12v Ground Input
- Antenna Wire